

安全鞋产品使用说明书

产品名称	防护性能
安全鞋	足趾保护(200J)+绝缘(6kV)

一、产品特点:

1. 采用优质牛皮,皮料的耐撕裂性及延展性都有优异的表现。
2. 鞋头的保护使用防砸包头,检验依据GB21148-2020标准6.2要求,本鞋可承受(200±4)J的冲击和(15±0.1)KN的静压,能有效保护足趾免受伤害。
3. 优质大底,具有耐磨、耐折、耐普通酸碱、轻便等优点(PU底的安全鞋不能用于有大量液体的工作场合)。
4. 内里材料为网布,透气性佳,同时使鞋子看上去具有立体感。
5. 鞋帮高度<103mm-121mm为低帮多功能安全鞋,轻巧方便、行动灵活、外形时尚;鞋帮高度≥103mm-121mm为中帮多功能安全鞋,鞋帮介于低帮与高帮之间,能更好的保护脚踝处不被扭伤。
6. 电绝缘性能:检验依据GB21148-2020标准6.4.3要求,测试工频电压6kV,试验时间1min,泄露电流≤1.8mA。
7. 防滑性:检验依据GB21148-2020标准5.2.5要求,在带有洗涤剂溶液的陶瓷砖面上,后跟向前滑动的摩擦系数大于等于0.28,水平向前滑动的摩擦系数大于等于0.32。
8. 多功能自由搭配、组合。

二、建议使用时间:

通常安全鞋的鞋底由PU材料或橡胶材料制成,这些材料随着时间、使用环境以及穿着者的穿着习惯在物理和化学特性上会产生变化,使得安全鞋的耐磨、胶粘牢度、硬度、舒适性等功能方面逐步减弱。因此,使用者(和仓管人员)应时常留意安全鞋的使用时间、鞋面、鞋底的磨损状况,一旦受到重压或重砸造成鞋内包头变形及鞋底出现软化,溶融等不得再作为安全鞋使用。

含电绝缘性能的安全鞋使用期限一般为24个月,对于存放超过24个月(自生产日期起计算)的鞋,须逐一进行电性能检验,只有符合GB21148-2020的6.4.3的鞋,方可继续销售和使用的。

三、产品应用:

适用于钢铁、建筑、电力、汽车制造、机械加工等作业场所。

四、注意事项:

1. 电绝缘鞋不能保证100%防护电击,且避免这种危险的附加测试是必需的。
2. 不耐强酸、强碱,不适用于经常接触化学品等有腐蚀性介质的场所。
3. 不能长期在高温、涉水环境下使用,否则会严重影响其使用寿命,甚至断底。
4. 定期清理安全鞋,但不应采用溶剂作清洁剂,同时要尽量避免用水直接冲洗,清洗时用软毛刷或微湿抹布去除鞋上灰尘与污物,然后置通风处晾干。

▲ 本产品属易耗品,不属于世达终身保用范围。

5. 面料为皮革时需经常给鞋面上油,防止皮革龟裂老化。
6. 鞋底亦须经常清扫,避免积聚污垢物,因鞋底的绝缘性能会受粘附污垢物多少和曲折情况而影响。
7. 在储存时,应存放在干燥通风的仓库内,存放温度不得超过50°C。绝缘鞋建议在(20±15)°C的环境中。防止霉变,堆放离开地面,墙壁0.2m以上,离开一切发热体1m以外。避免受油,酸碱类或其他腐蚀品的影响。
8. 使用者应根据使用场所与防护要求,选择相应的安全鞋。
9. 鞋在首次使用前和持续使用间隙之间应存放在一个适宜的盒子或容器中,不宜受压、折叠或靠近热源存放,不宜长时间暴露在阳光、人造光或其他臭氧源环境中,建议存放在(20±15)°C的环境中。每次使用前应仔细检查,如果发现机械或化学损伤,鞋不宜穿用。如有疑问,鞋必须进行耐压测试。鞋帮必须干燥。穿着者应检查鞋的耐压级别是否提供足够保护。鞋不宜在有切割、穿刺危险、可能降低绝缘性能的机械或化学侵犯的场所使用。在潮湿条件下穿用应特别注意。如果鞋变脏或被污染,特别是鞋帮,需要按照制造商推荐的方法清洁和干燥。
10. 为确保使用安全,应定期依据GB21148-2020的6.4.3检测鞋的电性能,如果没有相关规定,建议半年一次。

五、鞋垫:

产品均提供了可移动鞋垫,测试是鞋垫在鞋内时进行的,并且不允许有任何不与鞋底边缘贴合的操作(如移位、卷曲、滑动、尺寸不符等)。鞋只在适当位置使用鞋垫及鞋垫最好由原鞋制造商提供的同等鞋垫代替。

六、无害性申明及相关安全性信息:

我司产品选用的原材料以及加工制作过程的各种化学助剂,满足GB/T31009-2020中对限量物质要求和安全性要求的规定,并对上述声明内容及相关技术支撑文件的真实性、完整性、一致性负责。

七、执行标准:

GB21148-2020

Operation Instruction for Safety Shoes

Product Name	Protective Performance
Safety Shoes	Anti-Impact+Insulated

I. Product Features:

1. It is made of high-quality leather featuring excellent tear resistance and ductility.
2. Safety shoes using toe cap can effectively protect the toes from injury under pressure of (15±0.1)KN or impact energy of (200±4)J. Inspection according to the standard GB21148-2020 requirements of 6.2.
3. The high-quality outsole features good resistance to wear, folding, weak acids and alkali, and light weight, etc. (the safety shoes of PU sole are not suitable for a workplace containing a lot of liquid).
4. The lining material is mesh cloth, which has good air permeability and makes the shoes look three-dimensional.
5. If the height of the upper is less than 103-121mm, it is a pair of low-cut safety shoes which is light and stylish. If the height of the upper is no less than 103-121mm, it is a pair of middle-cut safety shoes with better protection of the ankles from sprains.
6. Insulation performance: Inspection according to the standard GB21148-2020 requirements of 6.4.3 requirements, test power frequency voltage 6kV, test time 1min, Leakage current ≤1.8mA.
7. Skid resistance: according to the standard GB21148-2020 requirements of 5.2.5, on the ceramic tile surface with detergent solution, the friction coefficient of heel sliding forward is greater than or equal to 0.28, and the friction coefficient of horizontal sliding forward is greater than or equal to 0.32.
8. The multi-function safety shoes can be used in any combination.

II. Recommended usage time:

Generally, the sole of safety shoes is made of PU or rubber. These materials will change in physical and chemical properties with time, using environment and wearer's wearing habits, gradually weakening the wear resistance, adhesive fastness, hardness, comfort and other functions of safety shoes. Therefore, The users (and the warehouse keepers) should always pay attention to the service time of safety shoes and the wear conditions of the upper and the sole. Once they are heavily pressed or smashed, resulting in deformation of toe cap in shoes and softening and melting of soles, they should not be used as safety shoes again.

The service life of insulated safety shoes is generally 24 months. For shoes stored more than 24 months (calculated from the production date), the electrical performance test must be carried out one by one. Only shoes that meet requirements 6.4.3 of GB21148-2020 can continue to be sold and used.

III. Application of product:

Suitable for steel, construction, electric power, automobile manufacturing, machining and other industries.

IV. Notes:

1. Insulated shoes do not guarantee 100% protection against electric shock, so additional tests to avoid this danger are necessary.
2. The shoes are not resistant to strong acid and alkali, and thus not suitable for places with frequent exposure to corrosive media such as chemicals.
3. The shoes cannot be used in environment with high temperature and wading environment for a long time, otherwise its service life will be seriously affected and even the bottom will be broken.

▲ This item is consumable, and is not covered under SATA lifetime warranty.

4. Clean the safety shoes regularly, but never use solvents as the cleaning agents. Try to avoid direct flushing with water. When cleaning, remove the dust and dirt on the shoes with a soft brush or slightly wet rag, and then place them in a ventilated place to dry.
5. In case of leather upper, apply oil to the upper on a regular basis, so as to prevent the leather from cracking and aging.
6. Always clean the sole frequently to avoid accumulation of dirt, which together with the folding condition may affect the insulating property.
7. During storage, it shall be stored in a dry and ventilated warehouse, and the storage temperature shall not exceed 50°C. The storage temperature of Insulated safety shoes is suggested during (20±15)°C. To prevent mildew the shoes should be stored more than 0.2m away from the ground and the wall, and 1m away from all heating elements. Avoid being affected by oil, acid, alkali or other corrosive products.
8. Users should select correct safety shoes according to the using place and protection requirements.
9. Shoes should be stored in a suitable box or container before first use and between continuous use. Do not store under pressure, folded or close to a heat source. Do not expose to sunlight, artificial light or other ozone for a long time. In the source environment, it is recommended that the storage device be stored at (20±15)°C. Check carefully before each use. If mechanical or chemical damage is found, shoes should not be worn. If in doubt, shoes must be pressure tested. The upper must keep dry. The wearer should check that the pressure rating of the shoe provides adequate protection. Shoes should not be used in areas where there is a risk of cutting, puncturing, mechanical or chemical intrusion that may reduce insulation. Special attention should be paid when wearing under wet conditions. If the shoe becomes dirty or contaminated, especially the upper, it needs to be cleaned and dried as recommended by the manufacturer.
10. In order to ensure the safety of use, electrical properties of shoes should be tested regularly according to the standard GB21148-2020 requirements of 6.4.3, if there is no regulation, it is suggested to be done every six months.

V. Shoe-pad(inside):

All products are provided with removable insole. The test was done with the insole inside the shoe. It is not allowed to operate insole that does not fit the edge of sole (such as displacement, curling, sliding, inconsistent size, etc.) Insoles should be used in the right place and the old insole had better be replaced by the same manufacturer.

VI. Harmlessness declaration and relevant safety information:

We here declare that the raw materials selected for our products and various chemical auxiliaries in the processing process meet the requirements of GB/T31009-2020. And responsible for the authenticity, integrity and consistency of the above statement and related technical supporting documents.

VII. Executive standard:

GB21148-2020